

IDM UID 8PD9A4
VERSION CREATED ON / VERSION / STATUS 28 Mar 2023 / 1.1 / Approved
EXTERNAL REFERENCE / VERSION

Design Report

Arrangement 5 - PHNB Low Flow Pump (26PHNB-PL-3000) Equipment Summary

This document compiles the main relevant information for the equipment identified in the document title

This document support activities for the preparation of Arrangement 5

<i>Approval Process</i>			
	<i>Name</i>	<i>Action</i>	<i>Affiliation</i>
<i>Author</i>	Giammei M.	28 Mar 2023:signed	IO/DG/CNST/PLD/MID/TCWS
<i>Co-Authors</i>	West S.	28 Mar 2023:signed	IO/DG/CNST/PLD/MID/TCWS
<i>Reviewers</i>	Berruyer F.	07 Apr 2023:recommended	IO/DG/CNST/PLD/MID/TCWS
	Ciampichetti A.	04 Apr 2023:recommended	IO/DG/CNST/PLD/MID/CMW
	Gao J.	06 Apr 2023:recommended	IO/DG/CORP/FPD/PCD/CAL
	Ghirelli N.	06 Apr 2023:recommended	IO/DG/CNST/PLD/MID/TCWS
	Ricou E.	28 Mar 2023:recommended	IO/DG/CNST/PLD/MID/TCWS
	Van hove W.	30 Mar 2023:recommended	ORNL - Oak Ridge National Laborator...
<i>Approver</i>	Lioce D.	07 Apr 2023:approved	IO/DG/CNST/PLD/MID/TCWS
<i>Document Security: Internal Use</i>			
<i>RO: Lioce Donato</i>			
<i>Read Access</i>	LG: Arrangement 5 Cost Estimation, LG: USDA Arrangement 5, LG: Management, GG: IO DDGs (and Senior Advisors), AD: IO_Director-General, AD: External Management Advisory Board, AD: OBS - Project Control Office (PCO), AD: IDM_Controller, AD: OBS - Procurement & Contracts Division (PCD), AD: Auditors, p...		


Change Log

Arrangement 5 - PHNB Low Flow Pump (26PHNB-PL-3000) Equipment Summary (8PD9A4)

<i>Version</i>	<i>Latest Status</i>	<i>Issue Date</i>	<i>Description of Change</i>
v1.0	Signed	13 Mar 2023	
v1.1	Approved	28 Mar 2023	New version to incorporate reviewers comments

OPERATIONAL NARRATIVE

PHNB Low Flow Pump provides cooling water to the Neutral Beam Injector in order to ensure a minimal flow during maintenance period.



Disclaimer:

- Contents of this document have been assembled, reviewed and approved as for Information Only,
- May not be used for purchasing, fabrication or construction,
- May not be used as verified input to any document (may be used as unverified assumption).

PHYSICAL ATTRIBUTES

<i>Commodity Type:</i>	PUMP
<i>Type:</i>	Canned motor pump
<i>Approx. Footprint:</i>	2.6 m x 1.3 m
<i>Approx. Height:</i>	Height: 1.2m (skirt/support included) Length: 2.6m Width: 1.3m
<i>Approx. Weight:</i>	3 000 kg (wet)
<i>Approx. Tank Volume:</i>	0.5 m ³
<i>Service Fluid:</i>	Demineralized Water
<i>Material Notes:</i>	304L with additional requirement Co < 0.2 w%, Nb < 0.1 w%, Ta < 0.05 w%
<i>Anchoring system</i>	PFM with Bolting
<i>Component configuration</i>	Skid
<i>Design Life Time:</i>	20 years

WBS: Primary Heat Transfer System

PBS: 26PHNB

GBS: 11-L4-04

REFERENCE DOCUMENTS

Sizing calculation: XF9LCC

PID: XH2WUB

ENVIRONMENTAL CONDITIONS

<i>Dose Rate:</i>	≤ 2 Gy/h
<i>Integrated Dose Rate 20yrs:</i>	≤ 10 000 Gy
<i>Magnetic Field:</i>	≤ 30 mT
<i>Normal temperature</i>	5 – 35 °C
<i>Normal Humidity</i>	20 – 60 %
<i>Normal Pressure relative to atm:</i>	-0.14 kPa
<i>Accidental Temperature</i>	130 °C
<i>Accidental Pressure relative to atm:</i>	-5 to +100 kPa
<i>Accidental Humidity</i>	100 %

DESIGN CODES AND SHIPPING

<i>French Law Pressure Category / Nuclear Class:</i>	Not Applicable
<i>European Law:</i>	Machine Directive (Directive 2006/42/EC)
<i>Fluid Type / Fluid group</i>	Liquid/ Group 2
<i>Conformity Assessment Module:</i>	N.A
<i>Related Codes:</i>	API 685
<i>Safety Class:</i>	SIC-2
<i>Quality Class:</i>	QC-1
<i>Seismic Class:</i>	SC1 (S)
<i>Fire:</i>	Eurocode 2h
<i>Shipping Information:</i>	Conventional Load (CTL), Oversea packing per ASME NQA-1 Level C, DAP at ITER site


PHNB – Low Flow Pump (26PHNB-PL-3000)

NOZZLE SCHEDULE

I.D.	DN / Schedule	Service
N1	200 / 20	Suction
N2	200 / 80S	Discharge
N3	25 / 40S	Drain

PARAMETERS

Parameter	Value
Nominal inlet Temperature (°C)	31
Design Temperature (°C)	100
Nominal inlet Pressure (MPa)	0.3
Design Pressure (MPa)	5.0
Nominal flow (m ³ /h)	375
Nominal Total Delivery Head @Nominal flow (mWC)	13.5
Nominal Total Delivery Head @No flow (mWC)	<15.0
Available NPSH @ Nominal flow (mWC)	26
Electrical power @ Nominal flow (kW)	< 43
Nominal electrical voltage (V)	400
Motor control principle	Direct On Line



Notes:

1. Approximate footprint is based on 3d model approved configuration.
2. All nozzles are flanged and a pipe stub of 300mm is requested to be provided.
3. Pump to be provided with dual temperature sensors on each bearing (applicable for both pump and motor), with vibration sensor on each bearing as well as dual temperature sensor for each motor phase.
4. Pump is mounted on a metallic platform (no grouting under the skid, no concrete plinth to attach the pump).
5. Fire: The equipment shall be insulated with fire resistant insulation against a Eurocode 2h fire. The insulation is included in the scope. The insulation thickness shall be sufficient to limit the metal temperature under the insulation to 240 °C. The uninsulated support structures shall be assumed to be at 400 °C. The supplier shall demonstrate resistance to the fire.
6. Nozzle loads: The nozzle loads are expected to be higher than the allowable nozzle loads from API 610. Provision should be taken to resist to high nozzle loads.